

FRAME BAND

SELF-EXPANDING SEALING TAPE FOR WINDOWS/DOORS



HERMETIC

Airtight and watertight, it interrupts possible acoustic bridges in the structure-window joint.

PRACTICAL

Thanks to the adhesive strip, application is easy and precise without the need for further glue.

TECHNICAL DATA

Properties	standard	value	USC conversion
Classification	DIN 18542	BG 1	-
Air permeability (α)	EN 12114	0 m ³ /(h·m·(daPa) ⁿ	-
Thermal conductivity (λ)	EN 12667	≤ 0,048 W/(m·K)	0.028 BTU/h·ft·°F
Water vapour transmission (Sd)	EN ISO 12572	indoor: 25 m outdoor: 0,5 m	-
Resistance to heavy rain	EN 1027	≥ 1050 Pa	-
Compatibility with other building materials	DIN 18542	compliant with class BG 1	-
Resistance to UV and weathering	DIN 18542	compliant with class BG 1	-
Reaction to fire class	DIN 4102-1	class B1	-
Acoustic insulation of joints R _{S,w} (ift)	EN ISO 10140-1 EN ISO 10140-2 EN ISO 717-1	18 mm: ≥ 63 (-2;-5) dB	-
Temperature resistance		-30 / +80 °C	-22 / +176 °F
Application temperature		≥ +5 °C	≥ +41 °F
Storage temperature ⁽¹⁾		+5 / +20 °C	+41 / +68 °F
Emicode	GEV test procedure	EC1 plus	-

⁽¹⁾Store the product in a cool, dry place for no more than 12 months.

Waste classification (2014/955/EU): 17 02 03.

CODES AND DIMENSIONS

CODE											
	B	s		s _{max}	L	B	s		s _{max}	L	
	[mm]	[mm]		[mm]	[m]	[in]	[mil]		[mil]	[ft]	
FRAME2054	54	2	12	20	30	2.1	79	472	787	98	7
FRAME2074	74	2	12	20	30	2.9	79	472	787	98	5



PROFESSIONAL INSTALLATION

Conforms with EnEV and RAL requirements, and guarantees a high level of thermal and acoustic insulation.

VERSATILE

It effectively seals any type of crack between 2 and 10 mm, resisting heavy rain.