

OUTSIDE GLUE

HIGH ELASTICITY UNIVERSAL ADHESIVE GLUE FOR EXTERNAL USE



ELASTIC

The butyl composition offers high joint elasticity over time, even in the case of small deformations or movements.

UNIVERSAL

Guarantees sealing and attachment to the most common materials, including damp or wet supports.



TECHNICAL DATA

Properties	value	USC conversion
Colour	grey	-
Composition	butyl rubber	-
Density	1,39 g/mL	222.9 oz/gal
Yield with strip Ø8 mm (cartridge 310 mL)	approx. 6 m	approx. 19.69 ft
Yield with strip Ø8 mm (cartridge 600 mL)	approx. 12 m	approx. 39.37 ft
Film formation time 20 °C / 50 %RH	20 - 30 min	-
Time required for complete hardening 20 °C / 50 %RH	4 - 6 weeks	-
Temperature resistance once hardened	-25 / +70 °C	-13 / +158 °F
Application temperature (cartridge)	+5 / +40 °C	-13 / +158 °F
Application temperature (ambient)	+5 / +40 °C	-13 / +158 °F
Application temperature (support)	+5 / +40 °C	-13 / +158 °F
Watertightness after hardening	conforming	-
Transport temperature	+5 / +30 °C	-13 / +86 °F
Storage temperature ⁽¹⁾	+5 / +25 °C	-13 / +77 °F
Storage time ⁽²⁾	up to 12 months	-


⁽¹⁾Store the product in a dry, covered location.

⁽²⁾Check the expiry date on the cartridge.

Waste classification (2014/955/EU): 08 04 10.

EUH066 Repeated exposure may cause skin dryness or cracking. EUH210 Safety data sheet available on request.

CODES AND DIMENSIONS

CODE	content [mL]	content [US fl oz]	version	
OUTGLUE310	310	10.48	rigid cartridge	24
OUTGLUE600	600	20.29	soft cartridge	12

■ FIELDS OF APPLICATION



WATER AND UV RESISTANT

The product offers excellent UV stability and is also suitable for sealing in the event of the presence of water during installation without the need for drying time.

DURABILITY

The modified butyl mix allows the product to remain elastic over time without altering its hermetic properties, even under high thermal stress.