

D 38 RLE

4-SPEED DRILL DRIVER

HIGH PERFORMANCE

Powerful and resistant 2000 W motor, able to reach a tightening torque of > 250 Nm at 1st speed.

Continuously variable speed adjustment in every gear.

MAINTENANCE-FREE

4-Speed transmission with continuous lubrication.

Convenient positioning of right/left rotation switching and speed regulator.



CODES AND DIMENSIONS

CODE	description	pcs
DUD38RLE	4-Speed drill driver	1

Scope of supply: 4-speed machine D 38 RLE, removal wedge in cardboard box. Use of the machine only with the safety clutch (DUVSKU) and the second grip (DUD38SH) is strongly recommended.

TECHNICAL DATA

Properties	values
Rated power consumption	2000 W
Drilling Ø on:	
- steel with solid drill bit	up to 32 mm 1 1/4"
- wood tip solid drill bit	up to 130 mm 5 1/8"
- polypropylene with LS hole cutter	up to 600 mm 23 5/8"
Rpm under load in 1st, 2nd, 3rd and 4th speed	120/210/380/650 U/min
Machine weight	8.6 kg 18.9 lbs
Collar diameter Ø	70 mm 2 3/4"
Drill chuck connection	conical MK 3



COMPLEMENTARY PRODUCTS - ACCESSORIES

FRICTION

- Tightening torque 200 Nm | 147.5 ft-lbs
- Square connection 1/2"

CODE	pcs
DUVSKU	1



SCREW HANDLE

- High security

CODE	pcs
DUD38SH	1



ADAPTER 1

- For MK3

CODE	pcs
DUD322	1



ADAPTER 2

- For sleeve

CODE	pcs
ATCS2010	1



SLEEVES

- For WB structural reinforcement system

CODE	Ø [mm]	Ø [in]	pcs
ATCS007	16	0.63	1
ATCS008	20	0.79	1



MANDREL

- Adapter 1 (DUD322) is required for connection to the D 38 RLE drill

CODE	pcs
DUF13	1



RTR STRUCTURAL REINFORCEMENT SYSTEM



For more information, see the "TIMBER SCREWS AND DECK FASTENING" catalogue, available in the "Catalogues" section of the website www.rothoblaas.com.