

KITE

ANCHOR POINT

VERSATILE

Ideal as an anchor point in multiple environments, it allows the operator to safely access.

SAFE

Laser cut from a single piece with no welding points, it improves safety in all its applications.

PRACTICAL

Thanks to its lightweight and compact size, this anchor can be installed quickly and easily.



EN 795:2012 A	UNI 11578:2015 A	OSHA 1926.502 (d)(15)	DrJ LST-2407- 116
---------------------	------------------------	-----------------------------	-------------------------



**MAXIMUM NUMBER
OF USERS**



LOAD DIRECTION



**TYPES OF
APPLICATION**



TECHNICAL DATA*

substructure	minimum thickness	fasteners	substructure	minimum thickness	fasteners
GL24h	100 x 100 mm	2 x HBS Ø8 1 x VGS Ø11	C20/25	140 mm	AB1 Ø12 M12 8.8 rod + ULS + MUT VIN-FIX HYB-FIX
S235JR	5 mm	EKS M12 8.8 + ULS + nut			

* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standards referred to. For a correct calculation report with minimum distances according to the standard requirements, the substructure must be checked by a qualified engineer before installation.

CODES AND DIMENSIONS

CODE	material		B [mm] [in]	L [mm] [in]	pcs	
KITE	AISI 430 stainless steel grade 1.4016		101 4	100 4	1	

ACCESSORIES

CODE	description
BEFKITE	KITE fastening set for timber