

BST

DRILLING STATION

- Collar diameter **Ø43 mm | 1 11/16"**
- Bit guide fastening: **8 - 30 mm | 5/16" - 1 3/16"**
- Tiltable version, adjustable up to 45° on both sides



MA961210/MA961211



MA961215/MA961216

CODES AND DIMENSIONS

CODE	description	pcs
MA961210	fixed BST 320 drilling station	1
MA961211	fixed BST 460 drilling station	1
MA961215	tiltable BST 460 S drilling station	1
MA961216	tiltable BST 650 S drilling station	1

TECHNICAL DATA

properties		BST 320	BST 460	BST 460 S	BST 650 S
Max. tool diameter at 0°	[mm] [in]	130 5 1/8	130 5 1/8	130 5 1/8	130 5 1/8
Max. tool diameter at 45°	[mm] [in]	-	-	100 4	100 4
Max. tip length	[mm] [in]	320 12 5/8	460 18 1/8	460 18 1/8	650 25 9/16
Max. hole depth	[mm] [in]	160 6 1/4	300 11 3/4	265 10 7/16	455 17 15/16
Weight	[kg] [lbs]	4,5 9.9	4,8 10.6	5 11.0	5,4 11.9



LEWIS
 TWIST DRILL BITS FOR DEEP DRILLING IN SOFT
 AND EUROPEAN HARDWOODS

See the product on page 236

