

BS 160 | BS 320 B



DRILLING COLUMN

ROBUST

Robust components ensure high quality and long service life.
Suitable for machines with a collar diameter of Ø43 mm.

PRECISE


The carriage control enables simple and precise operation.



DUBS160



DUBS320B



1



2

CODES AND DIMENSIONS

CODE	description	pcs
DUBS160	drilling column 160	1
DUBS320B	drilling column 320	1

COMPLEMENTARY PRODUCTS - ACCESSORIES

CODE	description	pcs
1 DUBFS2	fastening set (tightening drill chuck, lock nut, 25 impact anchors M12, washer M16)	1
2 DUTBS	dry suction adapter, designed for use with drilling supports equipped with hole cutters	1

TECHNICAL DATA

Properties	DUBS160	DUBS320B
Ø max. drilling	202 mm 8"	322 mm 12 11/16"
Ø max. drilling device with water recovery	182 mm 7 3/16"	-
Weight	12,2 kg 26.9 lbs	15,2 kg 33.5 lbs
Stroke	630 mm 25"	630 mm 25"
Column length	920 mm 36 1/4"	920 mm 36 1/4"
Tilt adjustment	0 - 45° no actuations	0 - 45° no actuations
Stand for device	with quick coupling	with quick coupling

