

# LEVEL BAND



## DAMP-PROOF COURSE FOR FOUNDATIONS

### WATERPROOF

It effectively blocks humidity due to capillary action, while offering excellent resistance to water, air and wind.

### VERSATILE

Available in three versions: ideal both as a wall barrier and to seal vertical wall - wall joints.



## TECHNICAL DATA




Properties	standard	value	USC units
Tensile strength MD/CD	EN 12311-2	≥ 20/≥ 20 N/mm <sup>2</sup>	≥ 2.9/≥ 2.9 lbf/mil <sup>2</sup>
Elongation MD/CD	EN 12311-2	≥ 550/≥ 600 %	-
Resistance to nail tearing MD/CD	EN 12310-1	≥ 120/≥ 120 N/mm <sup>2</sup>	≥ 17.4/≥ 17.4 lbf/mil <sup>2</sup>
Impact resistance	EN 12691	> 500 mm	-
Watertightness after artificial ageing	EN 1296 - EN 1931	compliant	-
Watertightness	EN 1928	compliant	-
Alkaline water vapour resistance	EN 1847 - EN 1931	compliant	-
Flexibility at low temperatures	EN 495-5	-30 °C	-22 °F
Resistance to temperature	-	-40/+90 °C	-40/+194 °F
Storage temperature <sup>(1)</sup>	-	+10/+25 °C	+50/+77 °F

<sup>(1)</sup>Store the product in a dry, covered location.

Waste classification (2014/955/EU): 17 02 03.

## CODES AND DIMENSIONS

CODE	B [mm]	s [mm]	L [m]	B [in]	s [mil]	L [ft]	
1 LEVEL085	85	0,17	25	3.4	7	82	2
2 LEVEL125	125	0,17	25	4.9	7	82	2
3 LEVEL350	350	0,17	25	13.8	7	82	2



### ADAPTABLE

The soft and elastic polyethylene profile allows it to be installed even in complex shapes and angles.

### COST-PERFORMANCE

The choice of materials and optimisation in production results in a solution that offers a good balance between performance and cost.